DUCHESNE COUNTY MONUMENT SURVEY RECORD

..95,90.00

FEN COR

00.15'12"

70, 2632.


LINE	BEARING	DISTANCE
L1	N 85°23'12" W	5.45
L2	S 03°42'28" E	5.88'

FOUND AN ALLRED SURVEYING 1½"
DIA. ALUMINUM CAP ON A
5/8"X24" REBAR WITH THE
ORIGINAL MARKED STONE SET
ALONGSIDE AT THE 1/4 CORNER

T1S R8W

SEC 9 | SEC 10 SEC 16 | SEC 15

U.S.B.&M.



NORTH

SCALE: 1"=30'

N 89°29'13" W **FENCE** 2647.85

FOUND A DUCHESNE COUNTY 2½"
DIA. ALUMINUM CAP ON A
5/8"X24" REBAR WITH THE
ORIGINAL MARKED STONE SET
ALONGSIDE AT THE 1/4 CORNER

SECTION CORNER

S 89°45'13" E

2645.62'

FOUND AN ALLRED SURVEYING 1½"
DIA. ALUMINUM CAP ON A
5/8"X24" REBAR WITH THE
ORIGINAL MARKED STONE SET
ALONGSIDE AT THE 1/4 CORNER

FOUND A DUCHESNE COUNTY 2½"
DIA. ALUMINUM CAP ON A
5/8"X24" REBAR WITH THE
ORIGINAL MARKED STONE SET
ALONGSIDE AT THE 1/4 CORNER



THE POSITION OF THIS CORNER WAS DETERMINED USING OLD EXISTING FENCE LINES INTERSECTION
AS THE BEST AVAILABLE EVIDENCE OF ITS LOCATION

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET DUCHESNE COUNTY 2½" DIA ALUMINUM CAP ON A 5/8"X24" REBAR 0.2' BELOW THE GROUND SURFACE ON THE SIDE OF A TWO-TRACK ROAD



CORNER MONUMENT MARKINGS

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7315385.644

F: 1839967.299 NAVD88 EL: 7140.19'

40°24'01.59222" N LATITUDE:

LONGITUDE: 110°47'00.36861" W

ELLIPSOID HEIGHT: 7091.36'

(GFOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0080W0_400500



PHOTO OF CORNER FACING S-W

CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>22 MAY'19</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

